



Henan DASION Machinery CO.,Ltd

E-mail:sales4@cndasion.com

Address:1509,pinganbaoxian,jingsanroad,jinshui street,zhengzhou,china

DXBS fine stone cement pump

Keywords: fine stone cement pump,concrete pump for sale

DXBS fine stone cement pump is designed similarly XBS fine stone concrete pump used for construction projects consisting of oil pump, oil tank, hydraulic valve, electric parts and Hydraulic rubber pipe joints etc. We also produce other type concrete pump for sale.

DXBS fine stone cement pump features

1. Engine: Chinese domestic diesel engine.
2. Main oil pump: Chinese domestic oil pump.
3. Main oil tank: Chinese domestic, seals adopt American Parker.
4. Hydraulic valve: Shanghai Lixin, Beijing Huade.
5. Electric parts: Main electric elements are from Schneider, Omron and LS brand.
6. Hydraulic rubber pipe joints: A complete set of hydraulic rubber pipe joints is provided by American Eaton.
7. 100m delivery pipeline, spare parts and maintenance tools.

DXBS fine stone cement pump images



Fine stone cement pump control panel includes electric switches for on/off, forward/reverse and agitator on/off. Hour meter is also located here along with E-stop, fuse panel and ignition switch. And the concrete pump for sale also includes twin-cylinder open loop all-hydraulic concrete pump which provides output up to 30cubic yards per hour with industry leading fuel efficiency.

concrete mixer



batching plants



concrete trucks



trailer pump



gunite machine



WEB:www.concretemixerschina.com

E-mail:sales4@cndasion.com



Henan DASION Machinery CO.,Ltd

E-mail:sales4@cndasion.com

Address:1509,pinganbaoxian,jingsanroad,jinshui street,zhengzhou,china

DXBS fine stone cement pump main technical specifications

	Items	Units	Models and Parameters	
			DXBS25-12-56	DXBS30-13-56
Performance Of The Machine	Theoretical Max. Discharging Volume	m ³ /h	25	30
	Theoretical Max. Delivery Pressure	Mpa	12	13
	Max. Delivery Frequency	times/min	24	30
	The Type Of Distribution Valve		S valve	S valve
	Outlet Opening Diameter	mm	Φ125	Φ125
	Hopper Capacity	L	300	300
	Main Motor Power	Kw	56	56
	Specification Of Delivery Cylinder	mm	Φ140×1200	Φ140×1200
	Specification Of Main Oil Cylinder	mm	Φ80/Φ50×1200	Φ80/Φ50×1200
Hydraulic System	Hydraulic Oil Circuit Type		Open Circuit	Open Circuit
	Max. Oil Pressure Of Pumping System	MPa	25	25
	Max. Oil Pressure Of Mixing System	MPa	9	9
	Max. Mixing Speed	r/min	24	24
	Oil Tank Capacity	L	200	200
Other Parameters	Max. Diameter Of Aggregates	mm	≤30 (≤20)	≤30 (≤20)
	Inner Dia. Of Delivery Pipe	mm	Φ100/Φ80	Φ100/Φ80
	Dimension (Length ×Width ×Height)	mm	4100×1500×1500	4300×1500×1500
	Overall Weight	Kg	2000	2100
	Pulling Speed	Km/h	≤8	≤8

concrete mixer



batching plants



concrete trucks



trailer pump



gunite machine



WEB:www.concretemixerschina.com

E-mail:sales4@cndasion.com